

FILTERS | AUTOMATIC SELF CLEANING SCREEN FILTERS |  
HYDRAULIC ODISMATIC FILTERS

**ODISMATIC 850 IN LINE - EXTENDED**



**Inlet Outlet  
Diameter**


50 mm / 2"  
80 mm / 3"  
100 mm / 4"  
150 mm / 6"

**Filtering Grade**

30 micron  
50 micron  
80 micron  
100 micron  
120 micron  
150 micron  
200 micron  
300 micron  
400 micron

**End Connection  
Type**

Flange  
Threaded



**Name Series  
Application**

OdisMatic 850 In Line  
Automatic Self Cleaning Screen Filter in places without electricity.  
Industrial waste water. Cooling towers process water. Process water.  
Water recycling. Municipal sewage. Pre filtration. For various  
industrial liquids, Sea water and Drinking water. Protection of  
hydraulic equipments like pumps valves and spraying nozzles.

**Inlet Outlet Diameter**  
**Max Flow Rate**  
**Max Pressure**  
**Min Working Pressure**  
**Filtering Grade**  
**Operation**  
**Control**

50 mm / 2" up to 150 mm / 6"  
25 m<sup>3</sup>/h / 110 gpm up to 150 m<sup>3</sup>/h / 660 gpm  
10 bar (150 psi)  
2 bar (30 psi)  
30 micron up to 400 microns  
Automatic  
Hydraulic, Manual