


FILTERS | AUTOMATIC SELF CLEANING SCREEN FILTERS |
HYDRAULIC ODISMATIC FILTERS

ODISMATIC 850 IN LINE - STANDARD



Inlet Outlet Diameter	Filtering Grade
-----------------------	-----------------

80 mm / 3"	30 micron
100 mm / 4"	50 micron
200 mm / 8"	80 micron
250 mm / 10"	100 micron
300 mm / 12"	120 micron
350 mm / 14"	150 micron
	200 micron
	300 micron
	400 micron



Name Series
Application

OdisMatic 850 In Line - Standard
Automatic Self Cleaning Screen Filter in places without electricity.
Industrial waste water. Cooling towers process water. Process water.
Water recycling. Municipal sewage. Pre filtration. For various industrial liquids, Sea water and Drinking water. Protection of hydraulic equipments like pumps valves and spraying nozzles.

Inlet Outlet Diameter
Max Flow Rate
Max Pressure
Min Working Pressure
Filtering Grade
Operation
Control

80 mm / 2" up to 350 mm / 14"
40 m³/h / 175 gpm up to 900 m³/h / 3960 gpm
10 bar (150 psi)
2 bar (30 psi)
30 micron up to 400 microns
Automatic
Hydraulic, Manual